

## COMPLETE FILTER

|   |  |                          |  |     |     |  |  |  |
|---|--|--------------------------|--|-----|-----|--|--|--|
| <b>Series and size</b>                  |  |                          | Configuration example 1: <span style="border: 1px solid black; padding: 2px;">RF2250</span> <span style="border: 1px solid black; padding: 2px;">W</span> <span style="border: 1px solid black; padding: 2px;">F2</span> <span style="border: 1px solid black; padding: 2px;">E</span> <span style="border: 1px solid black; padding: 2px;">M25</span> <span style="border: 1px solid black; padding: 2px;">P01</span> |     |     |  |  |  |
| RF2250                                  |  |                          | Configuration example 2: <span style="border: 1px solid black; padding: 2px;">RF2350</span> <span style="border: 1px solid black; padding: 2px;">A</span> <span style="border: 1px solid black; padding: 2px;">G1</span> <span style="border: 1px solid black; padding: 2px;">B</span> <span style="border: 1px solid black; padding: 2px;">A25</span> <span style="border: 1px solid black; padding: 2px;">P01</span> |     |     |  |  |  |
| RF2350                                  |  |                          |  |     |     |  |  |  |
|   |  |                          | Filtration rating  |     |     |  |  |  |
| <b>Seals and treatments</b>             |  |                          | Axx  | Mxx | Pxx |  |  |  |
| <b>A</b>                                | NBR                                    |                          | •  | •   | •   |  |  |  |
| <b>V</b>                                | FPM                                    |                          | •  | •   | •   |  |  |  |
| <b>W</b>                                | NBR compatible with fluids HFA-HFB-HFC |                          | •  | •   |     |  |  |  |
| <b>Z</b>                                | FPM compatible with fluids HFA-HFB-HFC |                          | •  | •   |     |  |  |  |
|   |  |                          | Connections  |     |     |  |  |  |
| <b>Connections</b>                      |  | Aux (only RF2350)        | Mxx  | Pxx |     |  |  |  |
| <b>G1</b>                               | G1 1/2"                                | G1"                      | •  | •   |     |  |  |  |
| <b>G2</b>                               | 1 1/2" NPT                             | -                        | •  |     |     |  |  |  |
| <b>G3</b>                               | SAE 24 - 1 7/8" - 12 UN                | SAE 16 - 1 5/16" - 12 UN | •  | •   |     |  |  |  |
| <b>G4</b>                               | G1 1/4"                                | -                        | •  |     |     |  |  |  |
| <b>G5</b>                               | 1 1/4" NPT                             | -                        | •  |     |     |  |  |  |
| <b>G6</b>                               | SAE 20 - 1 5/8" - 12 UN                | -                        | •  |     |     |  |  |  |
| <b>G7</b>                               | G1"                                    | -                        | •  |     |     |  |  |  |
| <b>G8</b>                               | 1" NPT                                 | -                        | •  |     |     |  |  |  |
| <b>G9</b>                               | SAE 16 - 1 5/16" - 12 UN               | -                        | •  |     |     |  |  |  |
| <b>F1</b>                               | 1 1/2" SAE 3000 psi/M                  | -                        | •  |     |     |  |  |  |
| <b>F2</b>                               | 1 1/2" SAE 3000 psi/UNC                | -                        | •  |     |     |  |  |  |
| <b>Bypass valve</b>                     |  |                          |  |     |     |  |  |  |
| <b>B</b>                                | 1.75 bar                               |                          |  |     |     |  |  |  |
| <b>E</b>                                | 3 bar                                  |                          |  |     |     |  |  |  |
| <b>Filtration rating (filter media)</b> |  |                          |  |     |     |  |  |  |
| <b>A03</b>                              | Inorganic microfiber 3 µm              | <b>M25</b>               | Wire mesh 25 µm  |     |     |  |  |  |
| <b>A06</b>                              | Inorganic microfiber 6 µm              | <b>M60</b>               | Wire mesh 60 µm  |     |     |  |  |  |
| <b>A10</b>                              | Inorganic microfiber 10 µm             | <b>M90</b>               | Wire mesh 90 µm  |     |     |  |  |  |
| <b>A16</b>                              | Inorganic microfiber 16 µm             | <b>P10</b>               | Resin impregnated paper 10 µm  |     |     |  |  |  |
| <b>A25</b>                              | Inorganic microfiber 25 µm             | <b>P25</b>               | Resin impregnated paper 25 µm  |     |     |  |  |  |
|   |  |                          | <b>Execution</b>   |     |     |  |  |  |
|   |  |                          | <b>P01</b> MP Filtri standard  |     |     |  |  |  |
|   |  |                          | <b>Pxx</b> Customized  |     |     |  |  |  |

## FILTER ELEMENT

|                                |                   |   |  |     |     |  |  |  |
|--------------------------------|-------------------|---|--|-----|-----|--|--|--|
| <b>Element series and size</b> |                   |   | Configuration example 1: <span style="border: 1px solid black; padding: 2px;">CU250</span> <span style="border: 1px solid black; padding: 2px;">M25</span> <span style="border: 1px solid black; padding: 2px;">W</span> <span style="border: 1px solid black; padding: 2px;">P01</span> |     |     |  |  |  |
| CU250                          |                   |   | Configuration example 2: <span style="border: 1px solid black; padding: 2px;">CU250</span> <span style="border: 1px solid black; padding: 2px;">A25</span> <span style="border: 1px solid black; padding: 2px;">N</span> <span style="border: 1px solid black; padding: 2px;">P01</span> |     |     |  |  |  |
|                                |                   |   | Filtration rating  |     |     |  |  |  |
| <b>Seals and treatments</b>    |                   |   | Axx  | Mxx | Pxx |  |  |  |
| <b>N</b>                       | NBR               |   | •  | •   | •   |  |  |  |
| <b>V</b>                       | FPM               |   | •  | •   | •   |  |  |  |
| <b>W</b>                       | NBR head anodized | filter element compatible with fluids HFA-HFB-HFC | •  | •   |     |  |  |  |
| <b>Z</b>                       | FPM head anodized |   | •  | •   |     |  |  |  |
|                                |                   |   | <b>Execution</b>   |     |     |  |  |  |
|                                |                   |   | <b>P01</b> MP Filtri standard  |     |     |  |  |  |
|                                |                   |   | <b>Pxx</b> Customized  |     |     |  |  |  |