

COMPLETE FILTER

Series and size	Configuration example 1:					
SF2500	SF2500	W	F1	D	M25	P01
SF2501	Configuration example 2:					
SF2503	SF2535	A	F2	C	M60	P01
SF2504						
SF2505						
SF2510						
SF2535						
SF2540						
Seals and treatments		Filtration rating				
A	NBR	Mxx	Pxx			
		•	•			
V	FPM					
		•	•			
W	NBR compatible with fluids HFA-HFB-HFC					
			•			
Z	FPM compatible with fluids HFA-HFB-HFC					
			•			
Connections						
	SF2500 - SF2505	SF2501 - SF2510	SF2503 - SF2535	SF2504 - SF2540		
F1	2" SAE 3000 psi/M	2 1/2" SAE 3000 psi/M	3" SAE 3000 psi/M	4" SAE 3000 psi/M		
F2	2" SAE 3000 psi/UNC	2 1/2" SAE 3000 psi/UNC	3" SAE 3000 psi/UNC	4" SAE 3000 psi/UNC		
C1	Hose barb 2"/M	Hose barb 2 1/2"/M	Hose barb 3"/M	Hose barb 4"/M		
Microswitch and Handwheel						
	SF2500 - SF2501	SF2503 - SF2504	SF2505 - SF2510	SF2535 - SF2540		
S	Without microswitch, without handwheel	•	•	•	•	
C	With microswitch, without handwheel			•	•	
D	With microswitch, with Nylon handwheel	•	•			
K	With microswitch, with steel handwheel	•	•			
M	Without microswitch, with Nylon handwheel	•	•			
Filtration rating (filter media)						
M25	Wire mesh 25 µm	M90	Wire mesh 90 µm			
M60	Wire mesh 60 µm	M250	Wire mesh 250 µm			

Execution
P01 MP Filtri standard
Pxx Customized

FILTER ELEMENT

Element series and size	Configuration example 1:				
SF503	SF510	M25	W	P01	
SF504	Configuration example 2:				
SF505	SF535	M60			P01
SF510					
SF535					
SF540					
Filtration rating (filter media)					
M25	Wire mesh 25 µm	M90	Wire mesh 90 µm		
M60	Wire mesh 60 µm	M250	Wire mesh 250 µm		
Seals and treatments					
	Standard version	Filtration rating	Mxx	Pxx	
			•	•	
W	Compatible with fluids HFA-HFB-HFC				
			•		

Execution
P01 MP Filtri standard
Pxx Customized